

Datasheet of Ribbon Tab Wire

Type	Width	Size	Thickness of copper base	Capacity of Max. current (A)	Package	KG/Meter	Meter/KG
		Thickness x Width					
Tab Wire	0.6	0.16*0.6	0.12	0.864	roll	0.0008256	1211.24031
		0.2*0.6	0.16	1.08	roll	0.001032	968.9922481
	0.8	0.08*0.8	0.05	0.576	roll/reel	0.0005376	1860.119048
		0.16*0.8	0.12	1.152	roll	0.0011008	908.4302326
	0.9	0.16*0.9	0.12	1.296	roll	0.0012384	807.4935401
		0.2*0.9	0.16	1.62	roll	0.001548	645.994832
	1.0	0.08*1.0	0.05	0.72	roll	0.000672	1488.095238
		0.16*1.0	0.12	1.44	roll	0.001376	726.744186
	1.2	0.1*1.2	0.07	1.08	roll	0.0001008	9920.634921
		0.12*1.2	0.8	1.296	roll	0.001224	816.9934641
		0.16*1.2	0.12	1.728	roll	0.0016512	605.620155
		0.2*1.2	0.16	2.16	roll	0.00204	490.1960784
	1.5	0.1*1.5	0.07	1.35	roll/reel	0.00126	793.6507937
	1.6	0.12*1.6	0.08	1.728	roll/reel	0.001632	612.745098
		0.16*1.6	0.12	2.304	reel	0.0022016	454.2151163
	2.0	0.1*2.0	0.07	1.8	roll/reel	0.0017	588.2352941
		0.12*2.0	0.08	2.16	roll/reel	0.002064	484.496124
		0.16*2.0	0.12	2.88	roll/reel	0.002752	363.372093
	3.0	0.12*3.0	0.08	3.24	reel	0.00306	326.7973856
Bus Wire	3.0 4.0 5.0 6.0 8.0	0.15*3.0	0.11	4.05	reel	0.003915	255.4278416
		0.15*4.0	0.11	5.4	reel	0.00522	191.5708812
		0.15*6.0	0.11	8.1	reel	0.00774	129.1989000
		0.15*8.0	0.11	10.8	reel	0.01032	96.8992200
		0.15*10	0.11	13.5	reel	0.01290	77.5193700
		0.12*13	0.11	14.0	reel	0.00134	74.5378600
		0.12*16	0.11	17.3	reel	0.01651	60.5620155
		0.2*3.0	0.16	5.4	reel	0.00522	191.5708812
		0.2*4.0	0.16	7.2	reel	0.00696	143.6781609
		0.2*5.0	0.16	9	reel	0.0087	114.9425287
		0.2*6.0	0.16	10.8	reel	0.01044	95.78544061
		0.2*8.0	0.16	14.4	reel	0.01392	71.83908046
		0.35*5.0	0.31	15.75	reel	0.015225	65.68144499
		0.35*6.0	0.31	18.9	reel	0.01827	54.73453749
		0.35*8.0	0.31	25.2	reel	0.02436	41.05090312