

**STAINLESS STEEL TIES SYSTEM**  
**Ball-Lock Polyester Coated Ties**


◎ 滚珠自锁式不锈钢喷带

**Pro-Fix**  
**Wiring Accessories**

**STAINLESS STEEL TIES SYSTEM**  
**Ball-Lock Polyester Coated Ties**

◎ 滚珠自锁式不锈钢喷带

**Pro-Fix**  
**Wiring Accessories**



**技术信息**

- ◇金属材料: 不锈钢材质304或316
- ◇喷塑材料: 环氧树脂粉末, 尼龙11
- ◇喷塑类型: 半喷、全喷、彩喷、带身喷
- ◇操作温度: -80℃~150℃
- ◇产品描述: 黑色带身及金属色搭扣
- ◇防火等级: 阻燃
- ◇材料特性: 抗紫外线无卤无毒

**产品特性**

- ◇金属色搭扣有利于区别于黑色尼龙扎带;
- ◇喷塑带身可以提供额外的边缘保护, 并避免金属间的腐蚀。

**Technical Information**

- ◇Material: Stainless Steel Grade 304 or 316
- ◇Coating: Polyester/Epoxy, Nylon 11
- ◇Working Temp.: -80°C to 150°C
- ◇Description: Black Band with Metallic Buckle
- ◇Flammability: Fireproof
- ◇Other Properties: UV-resistant, Halogen free, non toxic

**Product Feature**

- ◇Metallic buckle helps to distinguish from black nylon cable ties.
- ◇Polyester coated band provide additional edge protection, prevent the corrosion between dissimilar materials.

规格型号 Item No.	宽度 Width		长度 Length		厚度 Thickness		最大捆绑直径 Max.Bundle Dia.		最小捆绑直径 Min.Bundle Dia.		最小拉力 Min.Tensile Strength		配套工具 Recommended Installation Tool
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	N	lbs	

MGP-4.6*100	4.6	0.18	100	3.9	0.35	0.014	25	1.00	12.7	0.50	710	160	LQB LQG
MGP-4.6*150			150	5.9			37	1.46					
MGP-4.6*200			200	7.9			50	1.97					
MGP-4.6*250			250	9.8			63	2.48					
MGP-4.6*300			300	11.8			76	2.99					
MGP-4.6*350			350	13.8			89	3.50					
MGP-4.6*400			400	15.7			102	4.02					
MGP-4.6*450			450	17.7			115	4.53					
MGP-4.6*500			500	19.7			128	5.04					
MGP-4.6*550			550	21.7			141	5.55					
MGP-4.6*650			650	25.6			167	6.57					
MGP-4.6*800			800	31.5			193	7.60					

MGP-6.4*150	6.4	0.25	150	5.9	0.35	0.014	37	1.46	12.7	0.50	900	200	LQB LQG
MGP-6.4*200			200	7.9			50	1.97					
MGP-6.4*250			250	9.8			63	2.50					
MGP-6.4*300			300	11.8			76	3.00					
MGP-6.4*350			350	13.8			89	3.51					
MGP-6.4*400			400	15.7			102	4.00					
MGP-6.4*450			450	17.7			115	4.50					
MGP-6.4*500			500	19.7			128	5.00					
MGP-6.4*550			550	21.7			141	5.56					
MGP-6.4*600			600	23.6			160	6.30					
MGP-6.4*800			800	31.5			193	7.60					

规格型号 Item No.	宽度 Width		长度 Length		厚度 Thickness		最大捆绑直径 Max.Bundle Dia.		最小捆绑直径 Min.Bundle Dia.		最小拉力 Min.Tensile Strength		配套工具 Recommended Installation Tool
	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	N	lbs	
MGP-7.9*150	7.9	0.31	150	5.9	0.35	0.014	37	1.46	12.7	0.50	1112	250	LQB LQG
MGP-7.9*200			200	7.9			50	1.97					
MGP-7.9*250			250	9.8			63	2.50					
MGP-7.9*300			300	11.8			76	3.00					
MGP-7.9*350			350	13.8			89	3.50					
MGP-7.9*400			400	15.7			102	4.00					
MGP-7.9*450			450	17.7			115	4.50					
MGP-7.9*500			500	19.7			128	5.00					
MGP-7.9*550			550	21.7			141	5.56					
MGP-7.9*600			600	23.6			154	6.07					
MGP-7.9*650			650	25.6			167	6.58					
MGP-7.9*800			800	31.5			193	7.60					
MGP-7.9*1000			1000	39.4			206	8.12					

MGP-12*350	12	0.47	50	13.8	0.45	0.018	78	3.07	25.4	1.00	2000	450	LQA									
MGP-12*400			400	15.7			102	4.02														
MGP-12*500			500	19.7			128	5.04														
MGP-12*600			600	23.6			154	6.06														
MGP-12*750			750	29.5			188	7.40														
MGP-12*900			900	35.4			228	8.98														
MGP-12*1100			1100	43.3			278	10.94														
MGP-12.7*350			12.7	0.50			350	13.8						0.45	0.018	78	3.07	25.4	1.00	2000	450	LQA
MGP-12.7*400							400	15.7								102	4.02					
MGP-12.7*500							500	19.7								128	5.04					
MGP-12.7*600	600	23.6			154	6.06																
MGP-12.7*750	700	27.6			188	7.40																
MGP-12.7*900	900	35.4			228	8.98																
MGP-12.7*1100	1100	43.3			278	10.94																

MGP-15*350	15	0.59	350	13.8	0.45	0.018	78	3.07	25.4	1.00	3000	675	LQA
MGP-15*450			450	17.7			108	4.25					
MGP-15*600			600	23.6			148	5.83					
MGP-15*750			750	29.5			184	7.24					
MGP-15*900			900	35.4			220	8.66					
MGP-15*1100			1100	43.3			272	10.71					
MGP-15.9*350	15.9	0.63	350	13.8	0.45	0.018	78	3.07	25.4	1.00	3000	675	LQA
MGP-15.9*450			450	17.7			108	4.25					
MGP-15.9*600			600	23.7			148	5.83					
MGP-15.9*750			750	27.6			184	7.24					
MGP-15.9*900			900	31.5			220	8.66					
MGP-15.9*1100			1100	39.4			272	10.71					