

1500VDC MC4 Fuse Connector

产品规格:

Product Specifications:

绝缘材料 Insulation material	PPE/PA	保险丝电流 Fuse Current (Amp)	2A,3A,4A,5A,6A,8A,10A, 12A,15A,16A,20A,25A, 30A,32A,35A
额定电流 (不含保险丝) Rated current (Without fuse)	50A	安全等级 Safety degree	II
额定电压 Rated voltage	1500VDC	阻燃等级 Flame class	UL94-V0
最大的测试电压(含保险丝) Maximum voltage (With fuse)	1575V	环境温度范围 Ambient temperature range	-40°C...+85°C (IEC) *
连接器接触电阻 contact resistance	≤0.25 mΩ	温度上限 Upper limiting temperature	110°C (IEC)
金属导体材料 Contact material	铜,镀锡 Copper,Tin plated	适配电线规格 Suitable cable cross sections	2.5~10mm ² /14~8AWG
保护等级 Degree of protection	IP68(1m,1H)	适配保险丝尺寸 (mm) Suitable for fuse size(mm)	10*85mm
Rated Impulse voltage 额定脉冲电压	12KV	符合标准 Regulatory approval	TUV,CE

图示:

Drawing:

Part No.: RS-FH-1500V-X

(X is fuse ampere)

