






1		2		3		4		5		6		7																																																																																																																																																																																							
A																																																																																																																																																																																																			
MC4 Male to Female																																																																																																																																																																																																			
MC4 Male Connector				MC4 Female Connector																																																																																																																																																																																															
																																																																																																																																																																																																			
				Black 4.0mm ² L=2M																																																																																																																																																																																															
B																																																																																																																																																																																																			
C																																																																																																																																																																																																			
D																																																																																																																																																																																																			
E																																																																																																																																																																																																			
<table><tr><td colspan="2">Insulation material</td><td colspan="12">PP0</td></tr><tr><td colspan="2">Rated current</td><td colspan="12">30A</td></tr><tr><td colspan="2">Rated voltage</td><td colspan="12">1000V(TUV) 600V(UL)</td></tr><tr><td colspan="2">Test voltage</td><td colspan="12">6kV(50Hz,1min)</td></tr><tr><td colspan="2">Contact resistance</td><td colspan="12"><1mΩ</td></tr><tr><td colspan="2">Contact material</td><td colspan="12">Copper, Tin plated</td></tr><tr><td colspan="2">Degree of protection</td><td colspan="12">IP67</td></tr><tr><td colspan="2">Safety class</td><td colspan="12">II</td></tr><tr><td colspan="2">Flame class</td><td colspan="12">UL94-V0</td></tr><tr><td colspan="2">Insertion force</td><td colspan="12">Max. 50N</td></tr><tr><td colspan="2">Withdrawal force</td><td colspan="12">Min. 50N</td></tr><tr><td colspan="2">Ambient temperature range</td><td colspan="12">-40°C...+90°C(IEC)</td></tr><tr><td colspan="2">Cable size</td><td colspan="12">2.5mm2,4mm2,6mm2</td></tr></table>														Insulation material		PP0												Rated current		30A												Rated voltage		1000V(TUV) 600V(UL)												Test voltage		6kV(50Hz,1min)												Contact resistance		<1mΩ												Contact material		Copper, Tin plated												Degree of protection		IP67												Safety class		II												Flame class		UL94-V0												Insertion force		Max. 50N												Withdrawal force		Min. 50N												Ambient temperature range		-40°C...+90°C(IEC)												Cable size		2.5mm2,4mm2,6mm2											
Insulation material		PP0																																																																																																																																																																																																	
Rated current		30A																																																																																																																																																																																																	
Rated voltage		1000V(TUV) 600V(UL)																																																																																																																																																																																																	
Test voltage		6kV(50Hz,1min)																																																																																																																																																																																																	
Contact resistance		<1mΩ																																																																																																																																																																																																	
Contact material		Copper, Tin plated																																																																																																																																																																																																	
Degree of protection		IP67																																																																																																																																																																																																	
Safety class		II																																																																																																																																																																																																	
Flame class		UL94-V0																																																																																																																																																																																																	
Insertion force		Max. 50N																																																																																																																																																																																																	
Withdrawal force		Min. 50N																																																																																																																																																																																																	
Ambient temperature range		-40°C...+90°C(IEC)																																																																																																																																																																																																	
Cable size		2.5mm2,4mm2,6mm2																																																																																																																																																																																																	
<table><tr><td></td><td></td><td></td><td></td><td>尺寸公差</td><td>角度公差</td><td>核准</td><td>2020.4.10</td><td>材质</td><td colspan="3"></td><td>Product Name</td><td colspan="2">MC4 Extension Cable</td><td colspan="2" rowspan="4"> RISIN ENERGY CO., LIMITED</td></tr><tr><td></td><td></td><td></td><td></td><td>X.0 ±0.25</td><td>X.0° ±1°</td><td>审核</td><td>2020.4.10</td><td>表面处理</td><td colspan="3"></td><td>Part NO.</td><td colspan="2"></td></tr><tr><td></td><td></td><td></td><td></td><td>0.X ±0.13</td><td>0.X° ±0.5°</td><td>设计</td><td>2020.4.10</td><td>角法</td><td></td><td>比例</td><td colspan="2"></td><td>专案编号</td><td colspan="2"></td></tr><tr><td>版本</td><td>修订日期</td><td>修订内容</td><td>修订人</td><td>0.0X ±0.05</td><td>0.0X° ±0.2°</td><td>绘图</td><td>2020.4.10</td><td>页次</td><td></td><td>单位</td><td>mm</td><td></td><td>文件编号</td><td colspan="2"></td></tr><tr><td colspan="2">1</td><td colspan="2">2</td><td colspan="2">3</td><td colspan="2">4</td><td colspan="2">5</td><td colspan="2">6</td><td colspan="2">7</td></tr></table>																		尺寸公差	角度公差	核准	2020.4.10	材质				Product Name	MC4 Extension Cable		 RISIN ENERGY CO., LIMITED						X.0 ±0.25	X.0° ±1°	审核	2020.4.10	表面处理				Part NO.							0.X ±0.13	0.X° ±0.5°	设计	2020.4.10	角法		比例			专案编号			版本	修订日期	修订内容	修订人	0.0X ±0.05	0.0X° ±0.2°	绘图	2020.4.10	页次		单位	mm		文件编号			1		2		3		4		5		6		7																																																																																																									
				尺寸公差	角度公差	核准	2020.4.10	材质				Product Name	MC4 Extension Cable		 RISIN ENERGY CO., LIMITED																																																																																																																																																																																				
				X.0 ±0.25	X.0° ±1°	审核	2020.4.10	表面处理				Part NO.																																																																																																																																																																																							
				0.X ±0.13	0.X° ±0.5°	设计	2020.4.10	角法		比例			专案编号																																																																																																																																																																																						
版本	修订日期	修订内容	修订人	0.0X ±0.05	0.0X° ±0.2°	绘图	2020.4.10	页次		单位	mm		文件编号																																																																																																																																																																																						
1		2		3		4		5		6		7																																																																																																																																																																																							